

**TECHNICAL DATA SHEET****FloorWax Acrylic self-shining floor wax**

•

Flat, Semi-gloss, and Glossy protection for floors

Description	Acrylic wax to protect any flat surface where there's high foot traffic and walls finished with lime-based plaster or smooth cement
Composition	Synthetic wax emulsion dispersed in acrylic base
Where to apply	Any interior building surfaces, both flat and vertical
Colour	Milk white
Appearance	Liquid
Specific weight	1.05 ± 0.50 (gr/lt.)
Flammability	non-flammable
pH after 30 day	7.5 ± 020
Packaging	1.1 and 1.5 litre plastic jugs / bottles
Yield	average: with 1 litre, 24 sq. m. (1 coat)
Dilution	Ready to use, but can be diluted up to 100%.
Application temperature	min. 5° C, max 30° C. - Relative humidity < 85 %
Storage	36 months if in the original packaging and protected from excessive heat and cold. Keep from freezing.
Drying time	To the touch – 1 hour at 20° C



Surface – 4 hours
Completely - 24 hours

Safety measures Keep out of reach of children. In case of swallowing, consult a doctor.

VOC Classification Cat. A/ decorative paints. EU limit: 300g/l of COV.

This product contains :

Matt: 0 g/l of COV; Semiglossy 8,8 gr/l and Glossy 38,8 gr/l.

Application On clean, dry floors, apply one uniform coat of the desired product (flat, semi-gloss, or gloss) with a rag or felt wax applicator. After an hour, apply a second coat in a different direction than the first.

Generally it's recommended to apply it in thin coats since the excess wax might be visible and is easy to damage.

It can be walked on after an hour.

It is self-shining, but for maximum shine, polish it after several hours.

Maintenance Wash with EpoCleaner and re-apply the wax once a year or more often depending on wear.