

Technical Data sheet

MINERAL WAX

Mineral wax for continuous flooring

- Name: MINERAL WAX
- Description: MINERAL WAX FOR FLOOR COATINGS.
FINISH SUBJECT TO WEAR, USED FOR THE PROTECTION OF
DECORATIVE COATINGS
- Composition: Paraffins and micro-waxes
- Appearance: Thick milky paste
- Packaging: 1 litre

TECHNICAL DATA

Application: Manual

Dilution: Ready to use

Theoretical yield: ~ 25-30 gr / m²

Drying: 2 hours at 20 ° C to the touch
10 hours at 20 ° C in depth

Overcoat 2 hours at 20 ° C

Application temperature: min. 5 max 35 ° C. - RH <85% approx

VOC: As per Dir 2004 / As per Dir 2004/427 EC, Cat.A / c: Paintings for external walls of mineral substrate. Limit value for EU: 75gr./l. (2007) 40g / l. (2010). THIS PRODUCT CONTAINS 0.30 G / L. OF VOC.

Specific weight: 0,990 ± 10 (gr / LT.)

Flammability: Non-combustible

Storage: 36 months in its original packaging
The product retains best its characteristics if protected from excessive heat. Keep far from heat sources

Safety rules: Keep out of reach of children.

Disposal: The product must be disposed of according to the regulations in force on the matter. Empty containers must be sent to recycling.

APPLICATION

Apply by spatula or trowel in a minimum thickness. Wait at least one hour for polishing. This can be done manually or with electrical equipment. On the floor, it can be polished with a single disk machine. Avoid leaving excess or deposits. This treatment must be repeated periodically for the good maintenance of the coating. The wax can be regularly added, in small doses, to the water used for cleaning (in the form of liquid wax - to be requested separately).

This information is compiled on the basis of our best technical knowledge, nevertheless the suggestions and recommendations are provided without guarantee. The company reserves the right to make changes to this document without prior notice.