



STUCCO ITALIANO SRL

Via dell'Economia 117, Vicenza 36100 - Italia

Tel. +39 347 2469500 e-mail: info@stuccoitaliano.it

Specification Sheet

MOROCCAN SOAP SOAP FOR TADELAKT

Description	A special gel which acts as a protective barrier against water and dirt.
Composition	Water, olive oil, sodium carbonate.
Application fields	to protect: TADELAKT
Color	Amber.
Appearance	Thick paste
Specific weight	990 ± 20 gr. / lt.
Inflammability	non-flammable
pH after 30 days	8,2 ± 1
Packaging	kg 0,4 net polyethylene container
Theoretical Yield	gr./sq.m. 15- 20
Shelf live	36 months
Storage Suggestion	Product maintains its characteristics best if protected from extreme heat or cold
Safety Norms	In case of contact with eyes rinse with water. Keep out of reach of children.
Disposal	Product must be disposed of according to norms and regulations in force. Containers must be recycled.

Voc Classification: cat A/i decorative effect coating. EU limit value 300g/l of voc.

This product contains 0 g/l of Voc

APPLICATION NOTE:

For best results as a dirt repellent apply 24 hours after the stucco has been finished. Using a soft cloth or a sponge.

Apply a very thin layer of diluted soap all over the surface. Suggested dilution: 1 soap 5 parts of water.

Wipe off excess soap with a soft cloth before the material is completely dried or immediately after.

This soap is also used for protection of Beton Stucco or other lime based plaster when special effects are reserched.