

MR. CLAY WATER-BASED VARNISH "VARNISH No. 1"



TECHNICAL DATA SHEETS 1 / 2

About the product	A durable, top-quality water-based varnish, perfect for protecting clay plaster finishes when a durable, wet-cleanable surface is required. Suitable for use only on dry interior walls and in areas where there will be no prolonged contact with running water. The varnish is highly resistant to abrasion, alkalis, light, formaldehyde-free. Resistant to common cleaning agents. Easily varnished.
Classification according to DIN	Class SM, according to DIN 53778
IN 13 300	Wet abrasion resistance: Class 1
Usage recommendations	The varnish can be applied directly onto MR. CLAY clay mixtures. Greater resistance is achieved by applying varnish twice. It is recommended to apply varnish a second time only after the first coat of varnish has completely dried. The varnish must be mixed well before use. Apply varnish in short, directional movements, evenly and without rounding corners. It is recommended to use medium-length pile rollers for varnishing onto clay mixtures.
Color	Colorless
Binder	100% acrylic resin
Density	About 1.0-1.1 kg/l
Gloss level	Matte
Lacquer properties	<ul style="list-style-type: none">- The varnish is thick, so it absorbs into the surface more slowly and is easy to spread;- The dried varnish is completely matte, thus maintaining the appearance of natural clay plaster;- Like all varnishes, this one can slightly brighten/warm the final color of the walls.
Coverage	Depends on the application technique and surface: when applied with a roller on clay plaster 266-336 ml/m ² , on less absorbent surfaces 80-100 ml/m ² .
Basis	Suitable for clay mixtures, all new and old plasters, various types of concrete, plasterboard, fiberglass or non-woven wallpaper and many other surfaces.

MR. CLAY WATER-BASED VARNISH "VARNISH No. 1"



TECHNICAL DATA SHEETS 2 / 2

Surface preparation	The varnish can be applied directly to dried and hardened Mr. Clay clay plaster mixtures. Other Substrates for varnishing must be solid, clean, dry and prepared in accordance with applicable building regulations.
Working temperature	During varnishing, the air and substrate temperature must be at least +5°C.
Cleaning tools	Wash tools with water immediately after use.
Storage	The varnish will not dry after opening the package, but we recommend using it as soon as possible - within 3-7 days, as the composition uses gentle preservatives that do not ensure a long shelf life. Before closing the package for further use, clean the walls of the bucket and the lid so that the drying varnish film does not harden and fall into the remaining varnish. Store in a cool place.
Recycling	Only recycle completely empty packaging.
Package capacity	2 l
Safety and hazard information	The product is subject to the Hazardous Substances Ordinance. Information is contained in the safety data sheet in accordance with the CLP Regulation (GHS) and Regulation (EC) No. 1272/2008. All information can be found at any time at www.clay.lt or upon request by e-mail to vadyba@clay.lt It is necessary to comply with the labeling instructions on the packaging labels!
VOC content according to the VOC Directive Annex II to Directive 2004/42/EC	VOC limit value Annex II A (subcategory e) Permitted: max. 130 g/l according to stage II (2010) VOC content einzA mix Protect Finish: < 1.5 g/l
Manufacturer	Einza Farben GmbH & Co KG, Junkersstraße 13, 30179 Hanover www.einza.com
Distributor	Lietuvos prekybos kompanija, UAB Plytinės St. 1, Geistariškės, LT64234, Alytus District. +37060506540 www.clay.lt

The above information has been carefully compiled based on current knowledge and testing technology and is intended as a working guideline. Due to the application and different working methods, it is non-binding, does not create a contractual legal or other relationship and does not exempt the customer from testing our products. Otherwise, the general terms and conditions apply. The representative assumes no liability for damages if the product has been used improperly or for purposes other than those intended. We reserve the right to change the data provided without prior notice. Edition 06/2025; This means that all previous data sheets become invalid.